



Slagpluggen

ARTIKELGROEP 143

Slagpluggen/Kozijnpluggen

Nylon plug

RVS A2 schroef

Pozidrive

Nageldübel/Rahmendübel

Nylon Dübel

Schraub Stahl verzinkt 4.8

Pozidrive

Speedplug/ Nailplug

Nylon plug

Screw steel zincplated 4.8

Pozidrive

Diameter ϕ 5,0	L25	L30	L35	L40	L50	L60		
	V	V	V	V	V	V		
D2	3,4	3,4	3,4	3,4	3,4	3,4		
L plug	25	30	35	40	50	60		
L schroef	29	35	37	42	52	62		
S	5	5	5	5	5	5		
min. Boordiepte	30	30	30	30	30	30		
max. klembereik	5	10	15	20	30	40		

Diameter ϕ 6,0	L25	L30	L35	L40	L50	L60	L80	L100
	V	V	V	V	V	V	V	V
D2	4	4	4	4	4	4	4	4
L plug	25	30	35	40	50	60	80	100
L schroef	29	35	37	42	52	62	82	102
S	6	6	6	6	6	6	6	6
min. Boordiepte	35	35	35	35	35	35	35	35
max. klembereik	1	5	10	15	25	35	55	75

Diameter ϕ 8,0	L50	L60	L80	L100	L120	L140		
	V	V	V	V	V	V		
D2	5	5	5	5	5	5		
L plug	50	60	80	100	120	140		
L schroef	52	62	82	102	122	142		
S	8	8	8	8	8	8		
min. Boordiepte	50	50	50	50	50	50		
max. klembereik	10	20	40	60	80	100		

Overige uitvoeringen op aanvraag.