



## Blindklinknagels standaard alu / staal

### ARTIKELGROEP 170

Blindklinknagel

Blind niete

Rivets

Dome head

Flachkopf

Dome head

Aluminium / Staal

Aluminium / Stahl

Aluminium / Steel

Ook in RAL kleuren verkrijgbaar

Also in Ral-colors available

Auch mit RAL-Farben verfügbar

Dia.	2,4	3	3,2	4	4,8	5	6	6,4
D1	2,4	3	3,2	4	4,8	5	6	6,4
D2	5	6,5	6,5	8	9,5	9,5	12	13
k	0,55	0,8	0,8	1	1,1	1,1	1,5	1,8
d	1,45	1,8	1,8	2,2	2,75	2,75	3,2	3,6

Richtlijnen, per fabrikant afhankelijk

Guidelines, depends per manufacturer

Richtlinien vom Hersteller abhängig

D1 $\phi$ 2,4	klembereik	
L		
4	0,5 - 2,0	V
6	2,0 - 4,0	V
8	4,0 - 6,0	V
10	6,0 - 8,0	V

D1 $\phi$ 3,0	klembereik	
L		
5	0,5 - 2,5	V
6	1,5 - 3,5	V
7	1,5 - 4,5	V
8	3,5 - 5,5	V
10	5,5 - 7,0	V
12	7,0 - 9,0	V
14	9,0 - 11,0	V
16	11,0 - 13,0	V
18	13,0 - 15,0	V

D1 $\phi$ 3,2	klembereik	
L		
5	0,5 - 2,5	V
6	1,5 - 3,5	V
8	3,5 - 5,5	V
10	5,5 - 7,0	V
12	7,0 - 9,0	V
15	9,0 - 12,0	V

Scroll down for more

18	12,0 - 15,0	V
20	15,0 - 17,0	V
<b>D1 ø4,0</b>	<b>klembereik</b>	
L		
5	0,5 - 2,5	V
6	1,5 - 3,0	V
7	3,0 - 4,5	V
8	3,0 - 5,0	V
10	5,0 - 6,5	V
12	6,5 - 8,5	V
14	8,5 - 10,5	V
16	10,5 - 12,5	V
18	12,5 - 14,5	V
20	14,5 - 16,5	V
25	16,5 - 21,5	V
30	21,5 - 26,0	V
<b>D1 ø4,8</b>	<b>klembereik</b>	
L		
6	0,5 - 3,0	V
8	3,0 - 4,5	V
10	4,5 - 6,0	V
12	6,0 - 8,0	V
14	8,0 - 10,0	V
16	10,0 - 12,0	V
18	12,0 - 14,0	V
21	14,0 - 17,0	V
24	17,0 - 20,0	V
27	20,0 - 23,0	V
30	23,0 - 25,0	V
32	25,0 - 27,0	V
35	27,0 - 30,0	V
40	30,0 - 35,0	V
45	35,0 - 40,0	V
50	40,0 - 45,0	V
<b>D1 ø5,0</b>	<b>klembereik</b>	
L		
6	0,5 - 3,0	V
8	3,0 - 4,5	V
10	4,5 - 6,0	V
12	6,0 - 8,0	V
14	8,0 - 10,0	V
16	10,0 - 12,0	V
18	12,0 - 14,0	V
20	14,0 - 16,0	V
25	16,0 - 21,0	V
30	21,0 - 25,0	V
35	25,0 - 30,0	V
40	30,0 - 35,0	V
45	35,0 - 40,0	V
50	40,0 - 45,0	V

Scroll down for more

D1 ø6,0	klembereik	
L		
8	2,0 - 4,0	V
10	4,0 - 6,0	V
12	6,0 - 8,0	V
14	8,0 - 10,0	V
16	10,0 - 11,0	V
18	11,0 - 13,0	V
20	13,0 - 15,0	V
25	15,0 - 20,0	V
30	20,0 - 24,0	V
35	24,0 - 29,0	V
D1 ø6,4	klembereik	
L		
12	2,0 - 6,0	V
15	6,0 - 9,0	V
18	9,0 - 12,0	V
22	12,0 - 16,0	V
26	16,0 - 20,0	V
30	20,0 - 24,0	V
35	24,0 - 29,0	V
50	29,0 - 42,0	V



+31-(0)79 361 40 22



info@hofa.nl



hofa.nl